

ZKT_{ECO}

«**REGAL**»



PRODUCT GUIDE



COMPLETE SECURITY SOLUTION AT WWW.REGALSEcurity.CO.ZA

Access Control

ZKTeco's Access Control Product line is comprised of IP based standalone access control devices, networked access control panels, readers, and accessories with network based one-seat software.



LK171 **LK171-1**

F22 SilkID Fingerprint Reader & Keypad Black/White

- Fingerprints: 3 000
- Cards: 5 000
- Transactions: 30 000
- Authentication: FP / RFID / PIN
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 185mm x 78mm x 41 mm



**DURABILITY, RELIABILITY
AND AFFORDABILITY.**

LK168-10 **LK168-11** **LK168-12**

IN01A Fingerprint Keypad Reader, Built-in Battery

- Fingerprints: 3 000
- Cards: 10 000
- Transactions: 100 000
- Authentication: FP / PIN / RFID
- Communication: TCP/IP Wi-Fi RS485
- USB Host Client
- Features: ADMS Built-in 2000 mAh Battery Webserver
- Software: ZKAccess 3.5 / Third Party
- Dimensions: 222mm x 160mm x 48mm
- **LK168-11 - Wi-Fi**
- **LK168-12 - 4G**



LK169

X7 Fingerprint Reader & Keypad -Standalone

- Fingerprints: 500
- Cards: 500
- PIN: 8
- Authentication: FP / RFID / PIN
- Operation: Standalone ONLY
- Tokens: LK1 42 Tags & LK1 43
- Dimensions: 88.1 mm x 88.1 mm x 34.7mm



LK172-1

F16 Fingerprint Reader - IP65

- Fingerprints: 3 000
- Cards: 10 000
- Transactions: 30 000
- Authentication: FP / RFID
- Ingress Protection Rating: IP65
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 62.5mm x 185mm x 41.5mm



LK172-2

F17 Fingerprint Reader & Keypad - IP65

- Fingerprints: 3 000
- Cards: 10 000
- Transactions: 30 000
- Authentication: FP / RFID / PIN
- Ingress Protection Rating: IP65
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 62.5mm x 185mm x 41.5mm



LK172-4

ProCaptureWP SilkID Fingerprint Reader & Keypad - IP65

- Fingerprints: 20 000
- Cards: 10 000
- Transactions: 100 000
- Authentication: FP / RFID
- Ingress Protection Rating: IP65
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 97mm x 203mm x 35mm



LK179

MA300BT Fingerprint Reader - IP65 - Stainless

- Fingerprints: 1 500
- Cards: 10 000
- Transactions: 30 000
- Authentication: FP / RFID
- Ingress Protection Rating: IP65
- Communication: TCP/IP, RS485, Bluetooth & USB Host
- Software: ZKAccess 3.5
- Dimensions: 73mm x 148mm x 34.5mm



LK169-3

SF100 Fingerprint Reader

- Fingerprints: 1 500
- Cards: 5 000
- Transactions: 80 000
- Authentication: FP / RFID / PIN
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 90mm x 90mm x 35mm



LK169-4

SF300 Fingerprint Reader -Touch Screen

- Fingerprints: 1 500
- Cards: 5 000
- Transactions: 80 000
- Display: 2.8" Resistive Touch Screen
- Authentication: FP / RFID / PIN
- Communication: TCP/IP, RS485 & USB Host
- Software: ZKAccess 3.5
- Dimensions: 105mm x 105mm x 35mm



All Green Label products may be subject to licensing

Secondary Readers

Unlike primary readers, secondary readers are unintelligent readers that must consult their primary reader to grant or deny access. They do not manage a user or template database, therefore must be connected to a primary reader to be effective.



FR1500 Fingerprint Reader - SilkID - EM 125kHz - RS485

- Frequency : 125 kHz
- Authentication : FP / RFID
- Ingress Protection Rating : IP65
- Communication : RS485
- Dimensions : 122mm x 78mm x 38mm



LK187-9



F12ID Fingerprint Reader - EM 125kHz - RS485

- Frequency : 125 kHz
- Authentication : FP / RFID
- Ingress Protection Rating : IP65
- Communication : RS485
- Dimensions : 50mm x 107mm x 37mm



LK184-4



KR602 Proximity Reader- EM 125kHz Wiegand

- Frequency : 125 kHz
- Ingress Protection Rating: IP65
- Communication : Wiegand 26bit
- Power : 6 - 14VDC / Max 70mA
- Dimensions: 86mm x 86mm x 20mm



LK184-5



KR600 Proximity Reader- EM 125kHz Wiegand

- Frequency: 125 kHz
- Ingress Protection Rating : IP65
- Communication : Wiegand 26bit
- Power : 6 - 14VDC / Max 70mA
- Dimensions: 75mm x 116mm x 17mm



LK184-6



KR601 Proximity Reader-EM 125kHz Wiegand

- Frequency: 125 kHz
- Ingress Protection Rating: IP65
- Communication : Wiegand 26bit
- Power : 6 - 14VDC / Max 70mA
- Dimensions: 86mm x 86mm x 20mm



LK188-33



QR600HK QR Code Keypad ReaderEM 125kHz - Wiegand & RS485

- Frequency: 125 kHz
- Futures: Dynamic QR Code
- Ingress Protection Rating: IP65
- Software: BioSecurity
- Compatibility: Green Label
- Power : 12 VDC
- Dimensions: 80mmx120mmx23mm



LK184-1



KR101E Proximity Reader - EM 125kHz -Wiegand

- Frequency: 125 kHz
- Ingress Protection Rating: IP65
- Communication : Wiegand 26bit
- Power : 6 - 14VDC / Max 70mA
- Dimensions: 78mm x 43mm x 17mm



LK184-7



KR310 Proximity Reader - EM 125kHz & Mifare 13.56MHz-Wiegand

- Frequency: 125 kHz & 13.56 MHz
- Ingress Protection Rating: IP65
- Communication : Wiegand 26bit
- Power : 6 -14VDC / Max 70mA
- Dimensions: 77.5mm x 43mm x 17mm



LK184-9



PROID30 Proximity Reader Mifare - Wiegand

- Frequency: 125 kHz
- Ingress Protection Rating: IP65
- Connection : Wiegand 26bit
- Power: 7 - 13VDC / MAX 80 mA
- Dimensions: 90mm x90mmx16mm



LK184-10



PROID1 OBE Proximity Reader - EM 125kHz - Wiegand

- Frequency: 125 kHz
- Ingress Protection Rating: IP65
- Communication : Wiegand 26bit
- Power : 7 - 13VDC / Max 80mA
- Dimensions: 44mm x 80.5mm x 15mm



LK184-12



ProID20BE Proximity Reader - EM 125kHz - Wiegand

- Frequency : 125 kHz
- Ingress Protection Rating : IP65
- Communication : Wiegand 26bit
- Power : 7 - 13VDC / Max 80mA
- Dimensions : 90mm x 90mm x 16mm

DUAL FREQUENCY RFID WATERPROOF READER

RFID 125khz & MIFARE & 13.56Mhz

KR310

Dual frequency RFID Reader

ZKTeco

One Card Smart Solution

Hotel Locks, Visitors System, Time & Attendance,
Patrol Guard, Elevator Control, Entrance Control, Door Control,
Car Park systems and so much more



All Green Label products may be subject to licensing

Portable Terminals

ZKTeco's portable products offer a rugged, weather resistant, intelligent security solution. Specifically designed for off-site time management for the construction, farming, logistics and mining industries.

ZKTECO

Horus H1

Hybrid Biometric & QR code Handheld Mobile Time Attendance Terminal



5.5" Touch Screen



Embedded 5200mAh Li-Ion Battery



Android 10.0



IP65



NFC



QR Code



Fingerprint

Compatible with
ZKBio Time

Compatible with
ZKBio CVSecurity

LK168-3



LK168-1 LK168-2



S922W Fingerprint Keypad Reader - WiFi - Portable

- Fingerprints : 5 000
- Cards : 30 000
- Transactions : 200 000
- Authentication : FP / PIN
- Ingress Protection Rating : IP65
- Shock Resistant Enclosure
- Communication : TCP/IP 4G USB Host
- Software : Third Party
- Regal Security Technical support for TA hardware ONLY
- **LK168-2 - 4G**



LK168-3



ZKTeco Horus H1-FP Handheld Multi Biometric Reader - WIFI & 4G - IP65

- User Capacity : 50 000
- Face Capacity : 50 000
- Fingerprint Capacity : 30 000
- Card Capacity : 50 000 (NFC)
- Log Capacity : 1 000 000
- Ingress Protection : IP65
- Software : ZKBioTime or ZKBio CVSecurity

UHF Long Range Readers

The UHF RFID reader is a long-range card reader which can simultaneously read multiple passive UHF tags at ranges up to 12m. The reader is waterproof and is suitable for use in a wide range of RFID applications, such as transport management, vehicle management, car parking, production process and access control.



LK198-2

U2000E Stand Alone Long Range Reader -12m

- Cards : 5 000
- Antenna Gain : 8dBi
- Transactions : 30 000
- Authentication : UHF
- Frequency : 902 - 926 MHz
- Ingress Protection Rating : IP66
- Communication : TCP/IP
- Software : ZKAccess 3.5
- Dimensions : 445mm x 445mm x 70mm



LK198-3

U1000E Stand Alone Long Range Reader -6m

- Cards : 5 000
- Antenna Gain : 8dBi
- Transactions : 30 000
- Authentication : UHF
- Frequency : 902 - 926 MHz
- Ingress Protection Rating : IP66
- Communication : TCP/IP
- Software : ZKAccess 3.5
- Dimensions : 260mm x 260mm x 70mm



LK198

UHF2-1 OE UHF Reader-12m Wiegand

- Frequency : 902 - 926 MHz
- Antenna Gain : 8dBi
- Ingress Protection Rating : IP66
- Communication : Wiegand
- Dimensions : 445mm x 445mm x 70mm



LK198-8

UHF5E-Pro LED UHF Reader - 6m - Wiegand/RS485

- Frequency : 902 - 906 MHz
- Antenna Gain : 9dBi
- Ingress Protection Rating : IP67
- Communication : Wiegand 26bit or RS485
- Dimensions : 308mm x 308mm x 67mm



All Green Label products may be subject to licensing

Controllers

Centralized administration and web-based infrastructures reduce a company's IT costs and allows an easy management of all access points from one single location. For this purpose, ZKTeco offers a whole range of access control panels, that can manage from 1 to 4 doors using one or more identification modalities.

**LK186****C3-100 Door Controller-
One Door -RFID**

- Cards : 30 000
- Transactions : 100 000
- Authentication : RFID / PIN
- Inputs: 2 xWiegand, 1 x Door Sensor & 1 x RTE
- Outputs : 1 x Door Relay
- Auxiliary 1/0 : 1 x Out
- Communication: TCP/IP, RS485 & SD
- Software: ZKAccess 3.5

**LK187****InBio 160 Door Controller
- One Door - Fingerprint & RFID**

- Fingerprints: 3 000
- Cards: 30 000
- Transactions: 100 000
- Authentication: FP / RFID / PIN
- Inputs: 2 x Wiegand, 1 x Door Sensor & 1 x RTE
- Outputs : 1 x Door Relay
- Auxiliary 1/0: 1 x In & 1 x Out
- Communication :TCP/IP, RS485 & SD
- Software: ZKAccess 3.5

**LK187-1****InBio 260 Door Controller-
Two Doors-Fingerprint & RFID**

- Fingerprints: 3 000
- Cards : 30 000
- Transactions : 100 000
- Authentication : FP / RFID / PIN
- Inputs : 4 x Wiegand, 2 x Door Sensor & 2 x RTE
- Outputs : 2 x Door Relay
- Auxiliary 1/0: 2 x In & 2 x Out
- Communication :TCP/IP, RS485 & SD
- Software: ZKAccess 3.5

**LK187-2****InBio 460 Door Controller - Four
Doors - Fingerprint & RFID**

- Fingerprints: 3 000
- Cards: 30 000
- Transactions: 100 000
- Authentication: RFID / PIN
- Inputs: 4 x Wiegand, 2 x Door Sensor & 2 x RTE
- Outputs : 2 x Door Relay
- Auxiliary 1/0: 2 x In & 2 x Out
- Communication : TCP/IP, RS485 & SD
- Software: ZKAccess 3.5

**LK186-1****C3-200 Door Controller-
Two Door - RFID**

- Cards: 30 000
- Transactions: 100 000
- Authentication: RFID / PIN
- Inputs: 4 x Wiegand, 2 x Door Sensor & 2 x RTE
- Outputs : 2 x Door Relay
- Auxiliary 1/0: 2 x In & 2 x Out
- Communication : TCP/IP, RS485 & SD
- Software: ZKAccess 3.5

**LK197****InBio 260Pro One Door Controller
- One Door Green Label**

- Fingerprints : 20 000
- Cards: 30 000
- Transactions: 100 000
- Authentication: FP / RFID / PIN
- Inputs: 2 x Wiegand, 1 x Door Sensor & 1 x RTE
- Outputs : 1 x Door Relay
- Auxiliary 1/0: 1 x In & 1 x Out
- Communication :TCP/IP, RS485 & SD
- Software: BioSecurity

**LK197-1****InBio260Pro Door Controller
- Two Doors Green Label
Fingerprint & RFID**

- Fingerprints : 20 000
- Cards: 30 000
- Transactions : 100 000
- Authentication : FP / RFID / PIN
- Inputs: 4 x Wiegand, 2 x Door Sensor & 2 x RTE
- Outputs : 2 x Door Relay
- Auxiliary 1/0: 2 x In & 2 x Out
- Communication: TCP/IP, RS485 & SD
- Software: BioSecurity

**LK197-2****InBio460Pro Door Controller
- Four Doors Green Label**

- Fingerprints: 20 000
- Cards: 30 000
- Transactions: 100 000
- Authentication: FP / RFID / PIN
- Inputs: 4 x Wiegand, 4 x Door Sensor & 4 x RTE
- Outputs : 4 x Door Relay
- Auxiliary 1/0: 4 x In & 4 x Out
- Communication : TCP/IP, RS485 & SD
- Software: BioSecurity

**LK189-7****ECI O Elevator Controller-
Green Label**

- Floor Support: 10
- Fingerprints : 3 000
- Cards: 30 000
- Transactions: 100 000
- Communication :TCP/IP & RS485
- Supports: 3 x EXI 6
- Software: BioSecurity
- Dimensions: 242mm x 95mm x 60mm

**LK189-8****EXI 6 Elevator Extension
Board - Green Label
Fingerprint & RFID**

- Floor Support: 16
- Communication: RS485
- Software: BioSecurity
- Dimensions: 160 mm x 106mm x 60mm

**Easy
management
controllers****ZKTeco****LK197-9**

All Green Label products may be subject to licensing

Facial Recognition

Facial recognition is a category of biometric software or hardware that maps an individual's facial features mathematically and stores the data as a faceprint. The system uses either ZKTeco's deep learning or the standard ZKFace algorithms to compare a live capture of the stored faceprint in order to verify an individual's identity.



LK188-34

ProMA Multi-Biometric Reader - Face Fingerprint - IP66

- Faces : 30 000
- Fingerprints : 10 000
- Cards : 50 000
- Transactions : 500 000
- Algorithm : VLDeepLearning
- Authentication : Face / FP / RFID
- Ingress Protection : IP66
- Vandal Resistant : IK07
- Communication : TCP/IP, RS485 Wiegand
- Software : Bio CVSecurity
- Dimensions : 194.7mm x 68.7mm x 28.3mm



LK188-8

SpeedFaceVSLP Visible Light Multi-Biometric Reader

- Faces : 6 000
- Palms : 3 000
- Fingerprints : 10 000
- Cards : 10 000
- Transactions : 200 000
- Algorithm : ZKLiveFace V5.8
- Authentication : Face/ FP / RFID / PIN/ PALM
- Communication : TCP/IP, RS485 & USB Host
- Software : Bio CVSecurity
- Dimensions : 203mm x 92mm x 22mm



LK188-17

ProFaceXP Multi-Biometric Reader - Iface and Palm

- Faces : 30 000
- Palm : 3 000
- Transactions : 1 000 000
- Display : 8" Touch
- Algorithm : ZKFace V5.8 & ZKPalm VI 2.0
- Ingress Protection : IP68
- Vandal Resistant : IK04
- Authentication : Face/ Palm
- Communication : TCP/IP, RS485 & USB Host
- Software : Bio CVSecurity



LK188-15

SpeedFace RFID Multi-Biometric Reader - Face and Palm

- Face : 6000
- Palm : 3000
- Card : 10 000
- Transactions : 200 000
- Algorithm : VLDeep Learning
- Authentication : Face/ Pin/ RFID / Palm
- Communication : TCP/IP, RS485 & USB Host
- Software : Bio CVSecurity
- Dimensions : 203mm x 92mm x 22mm



LK188-31

Speed Face M4 Multi-Biometric Reader - Face, & Palm

- Face : 6000
- Palm : 3000
- Transactions : 200 000
- Display : 5" Touch
- Algorithm : ZKFace V5.8 & ZKPalm VI 2.0
- Authentication : Face/ Pin/ RFID / Palm
- Ingress Protection : IP66
- Communication : TCP/IP, RS485, WIFI & USB Host
- Software : Bio CVSecurity
- Dimensions : 213mm x 104mm x 51 mm



LK188-30

SpeedFace Mini Multi-Biometric Reader - Face, Palm & QR Code

- Face : 800
- Palm : 800
- Card : 10 000
- Transactions : 150 000
- Algorithm : ZKFace V5.8 & ZKPalm VI 2.0
- Authentication : Face/ Pin/ RFID / QR Code
- Communication : TCP/IP, RS485 & USB Host
- Software : Bio CVSecurity
- Dimensions : 158mm x 73mm x 23mm



LK171-2

MB600 Multi-Biometric Keypad Reader - Fingerprint Face - WiFi

- Faces : 800
- Fingerprints : 3 000
- Cards : 5 000
- Transactions : 100 000
- Authentication : FACE / FP / RFID / PIN
- Communication : WIFI / TCP/IP RS485 USB Host
- Software : ZKAccess 3.5
- Dimensions : 174mm x 98mm x 60mm



LK188-13

FaceKioskH13 Facial Recognition - VisibleLight - Kiosk Only

- Faces : 10 000
- Fingerprints : 10 000
- Transactions : 100 000
- Display : 13.3 Touch
- Algorithm : VLDeepLearning
- Authentication : Face / FP / RFID / PIN / QR
- Communication : TCP/IP RS485 WIFI Bluetooth USB Host
- Software : Bio CVSecurity
- Dimensions : 1500mm x 400mm x 400mm

Smart Locks

Smart lock is an electromechanical lock which allows you to open and lock your doors with a virtual key or fingerprint, face or RFID card, putting an end to the problem of lost keys and enabling an array of intelligent and useful features. Introducing ZKTeco's cutting edge biometric technology which provides security and convenience for your home and office.

Hotel Locks



LK174-9L LK174-9R

ZL500 Wireless Hotel Lock

- Mortise : American Standard Mortise with 5 Latches
- Unlocking Method: Card / App / Mechanical Key
- Communication: Zig Bee
- Power: 4 X AA Alkaline Batteries
- Certification : CE-RED
- Software: ZKBioHLMS
- Compatible door thickness: 35mm to 45mm
- Dimensions: 298mm x70mm x20mm



LK174-10

SLG410 Zig bee Gateway - Hotel

- Operation : For use with ZLS00
- Communication : Zig Bee & WiFi
- Max Connection Nodes: 10
- Power : 5V DC 1 A (Micro-USB)
- Dimensions: 90mm x 90mm x 22mm



LK174-11

DI 47-H Card Encoder - Hotel 13.56MHz

- Operation : For use with ZKBioHLMS
- Frequency: 13.56MHz
- Tokens: Mi Fare S50 / S70 / DESFire / NTAG216 / Ultralight / FM 1204 / FM 1208
- Power : 5V DC 1 A (USB)
- Dimensions: 107mmx107mm x23mm

Smart Locks



LK174-5

TL400-B Smart Door Lock - Fingerprint - Bluetooth

- Fingerprints : 100
- Cards: 100
- Unlocking Method : FP / RFID / PIN / APP / Mechanical Key
- Communication: Bluetooth (BLE4.0)
- Power: 4 x AA Alkaline Batteries
- Features: Remote Visitor Password, Zinc Alloy Casing
- Compatible Door Thickness: 35mm-50mm
- Dimension : 310mm x 72mm x 34mm (Excluding Handle)



LK175-10

ML100 Smart Door Lock - Fingerprint Keypad Reader - Wi-Fi


- Users : 300
- Unlocking Method : FP / PIN / Card / APP / Mechanical Key
- Communication : Wi-Fi
- Power : 4 AA Alkaline Battery (not included)
- Features : Reversible Handle & Remote Visitor Password
- Mobile App : ZSmart App
- Compatibility Door Thickness : 35mm to 60mm



LK193-6

VR10 Pro Vehicle Detection Radar Sensor


- Detection Distance : 1m - 6m
- Power : DC 10V - 16V
- Interface : Bluetooth, RS485, Relay
- Ingress Protection Rating : IP67
- Supported App : Radar Assistant
- Dimensions: (Case) 107.5mm x 73.2mm x 18mm



LK487-1L/R

BG 1145 Parking Folding Barrier -3.5m Incl. UPS

- Motor Type : 24V brushed DC
- Boom Type : Folding
- Boom Length : 3.5m
- Operation Speed : <0.5s
- Ingress Protection Rating: IP54
- Power Consumption: 120W
- Dimensions: (Case) 350mm x 300mm x 1020mm



LK487-2R/L

BG1145 Parking Barrier - 4.5m Boom -Incl. UPS

- Motor Type: 24V brushed DC
- Boom Type: Straight Telescopic
- Boom Length : 4.5m
- Operation Speed : <0.5s
- Ingress Protection Rating: IP54
- Power Consumption: 120W
- Dimensions: (Case) 350mm x 300mm x1020mm

Your one stop security shop

From our warehouse to your front door

Delivery available across SA

Quotes are customised for your business

Secure payment gateway

www.regalsecurity.co.za | National Support Centre: 087 802 3920

Entrance Control

Entrance control is the management of people. In different environments, different types of entrance control devices are required. ZKTeco commits to integrating biometrics into entrance control to provide more intelligent management solutions.

Also available in
4 arm



LK187-3

FHT2300 Turnstile - Full Height - 3 Arm - Blank

- Ingress Protection Rating: IP54
- Power: 220VAC
- Enclosure: SUS304
- Dimensions: 1400mm x 1395mm x 2220mm

LK187-7

FHT2322 Turnstile - Full Height - 3 Arm - Fingerprint RFID

- Fingerprints: 3000
- Transactions: 100 000
- Authentication: FP / RFID
- External Reader: LK187-8 built-in
- Controller: LK187-1 built-in
- Ingress Protection Rating: IP54
- Power: 220VAC
- Enclosure: SUS304
- Dimensions: 2220mm 2018mm 1397mm



LK187-4

TS2000Pro Waist High Turnstile Bi-Directional Bridge Drop Arm

- Power: 220VAC
- Enclosure: SUS304
- Dimensions: 1110mm x 980mm x 260mm + arm length 500mm



LK187-5

TS2022Pro Waist High Turnstile - FP & RFID Drop Arm

- Fingerprints: 3 000
- Transactions: 100 000
- Authentication: FP / RFID
- External Reader: LK1 87-9 (built-in)
- Power: 220VAC
- Software: ZKBio CVSecurity
- Enclosure: SUS304
- Dimensions: 1110mm x 980mm x 260mm + arm length 500mm



LK187-4-1

TS1000Pro Turnstile - Waist High - Drop Arm

- Power: 220VAC
- Enclosure: SUS304
- Dimensions: 1010mm x 520mm x 310mm arm length 500mm



LK187-12

TS1022Pro Turnstile - Waist High - Drop Arm FP & RFID

- Fingerprints: 3 000
- Transactions: 100 000
- Authentication: FP / RFID
- External Reader: LK1 87-9 (built-in)
- Power: 220VAC
- Software: ZKBio CVSecurity
- Enclosure: SUS304
- Dimensions: 520mm x 310mm x 1010mm + arm length 500mm



LK143

Proximity Card - EM 125kHz

- Frequency: 125 kHz
- Features: PVC with code

LK145

Proximity Card 1K Mifare 13.56Mhz

- Frequency: 13.56 MHz
- Tokens: Mifare S70 4K
- Features: PVC, Blank

LK141

Proximity Card - 4K S70 - Mifare 13.56Mhz

- Frequency: 13.56 MHz
- Tokens: Mifare S70 4K
- Features: PVC, Blank

LK143-3

Proximity Card -UHF 915MHz

- Frequency: 915 MHz
- Features: PVC, Blank

LK142-6

Proximity Card - EM 125kHz & UHF 915MHz

- Frequency: 125 kHz & 915 MHz (UHF)
- Features: PVC, Blank
- Operation: For use with all EM and UHF readers



LK142-3

Higgs-4 Proximity Tag - Higgs-4 Windscreen Tag -UHF 915MHz

- Frequency: 915 MHz
- Operation: For use with UHF readers



LK142-4

UHF1 /TAG2 Proximity Tag - Sticker -UHF 915MHz

- Frequency: 915 MHz
- Operation: For use with UHF readers



LK142-5

UHF1 /TAG3 Proximity Tag - Licence Plate Bar - UHF 915MHz

- Frequency: 915 MHz
- Operation: For use with UHF readers



LK142

ProximityTag - EM 125kHz - Black



LK142-1

ProximityTag - EM 125kHz - Blue



LK142-9

1K S50 - Mifare 13.56Mhz - Grey



LK142-10

4K S70 - Mifare 13.56Mhz - Grey

Security & Inspection Control

ZKTeco's security inspection products offer a dependable and flexible intelligence security solution. We built a comprehensive security system to protect your entrance security, including People Inspection, Freight Inspection.



LK230

X6550 X-Ray Inspection System

- Tunnel Size: 660mm x 510mm
- Tube Voltage: 150 Kv
- Dosage : < 1 uGy
- Wire Resolution : 40AWG
- Penetration : 38mm Steel Board
- Film Safety: ASNISO 1600
- Monitor: 17" LED
- Dimensions: 2200mm x 1135mm x 1515mm
- Weight: 785KG



LK230-2

X6550A X-Ray Machine

- Tunnel Size: 655mm x 505mm
- Tube Voltage: 100 Kv
- Dosage : < 1 uGy
- Wire Resolution : 34 AWG
- Penetration : 10mm Steel Board
- Film Safety: ASNISO 1600
- Monitor: 21 .5"LED
- Dimensions: 1755mm x 2240mm x 1170mm
- Weight: 740KG



LK230-1

X5030A X-Ray Machine

- Tunnel Size: 507mm x 305mm
- Tube Voltage: 80 Kv
- Dosage : < 1 uGy
- Wire Resolution : 34AWG
- Penetration : 8mm Steel Board
- Film Safety: ASNISO 1600
- Monitor: 17" LED
- Dimensions: 1900mm x 990mm x 1320mm
- Weight: 410KG



BD100

D1065S -Walkthrough Metal Detector - 6 Zone

- Zones: 6
- Display: Monochrome LCD
- Frequency: 4 - 8 kHz
- Features : 100 Sensitivity Levels per Zone, Alarm & People Counter
- Power: 100 - 240 VAC 50/60Hz
- Dimensions: 2200mm x 800mm x 580mm



BD04-2

DI80K Hand Held Metal Detector - Battery & Charger

- Frequency: 25 kHz
- Features: Low Sensitivity Selector, Audio Visual Indicator
- Power: 7 - 9 VDC
- Dimensions: 410mm x 85mm x 45mm
- Includes: Battery and Charger



BD100-1

D2180 -Walkthrough Metal Detector - 18 Zone

- Zones: 18
- Display: 5.7" LCD
- Frequency: 4 - 8 kHz
- Features: 256 Sensitivity Levels per Zone, Alarm & People Counter
- Power: 100 - 240 VAC 50/60Hz
- Dimensions: 2200mm x 800mm x 580mm



LK100-2

D4330 -Walkthrough Metal Detector - 33 Zone

- Zones: 33
- Display: 7" LCD
- Frequency: 4 - 8 kHz
- Features: 300 Sensitivity Levels per Zone, Alarm & People Counter
- Power: 100 - 240 VAC 50/60Hz
- Dimensions: 2200mm x 930mm x 760mm

ZKTeco

ZK-D4330
Walkthrough
Metal Detectors

Inspection Security Solutions
to Increase the Security at Airports

ZKTeco offers Outstanding Security Inspection Solutions to improve the security and operational efficiency at airports.

www.zkteco.co.za sales@zkteco.co.za

Enrollment Readers

During Enrollment, biometric or token information is captured and stored. In subsequent uses, the information presented at the reader is compared with the information stored at the time of enrollment.



LK185-1

CR20M Take-on Reader - Mifare 13.56MHz-USB

- Frequency: 13.56 MHz
- Communication : USB
- Operation : Take-on Reader for ZKAccess 3.5 Or BioSecurity
- Power : 5VDC
- Features: Audible Buzzer, LED Green and Red



LK185-4

CR20E Take-on Reader - EM 125kHz - USB

- Frequency : 125 kHz
- Communication : USB
- Operation : Take-On Reader for ZKAccess 3.5 Or BioSecurity
- Tokens : LK142 Tags LK143 Cards
- Power : 5VDC
- Features : Audible Buzzer LED Green and Red



LK185-3

SLK20R SilkID Fingerprint Enrollment Device - USB

- Communication: USB
- Operation : Enrollment Reader for ZKAccess 3.5 Or BioSecurity
- Power : 5VDC
- Features: FAP20 resolution, PIV Certified, Liveness Detection
- ISO-19794-2/4 ANSI-378 Standards Supported
- Dark Field Illumination & Skin Optical Signature recognition



LK185-5

PV10R Enrollment - Palm - USB

- Communication : USB
- Operation : Enrolment Device for ZKAccess 3.5 Or BioSecurity
- Power : 5VDC
- Features : Palm Enrollment

LK185-8

UR 20RW-E Take-on-Reader UHF-USB Device - USB

- Communication : USB
- Operation : Enrollment Reader for ZKAccess 3.5
- Power : 5VDC
- Features : Microsoft Windows 2000, XP, 7, 8.1 & 10 compatible



LK198-6

UR 20RW-E Take-on-Reader UHF-USB Device - USB

- Frequency: 865 - 868MHz
- Communication : USB
- Operation : Take on UHF Reader for ZKAccess 3.5 or BioSecurity

Accessories

These accessories are essential to complete your access control solution. Whether it is a card, a tag or a bracket. Brackets are an ideal solution when it comes to cable management as well as protecting your device from the elements.



LK171-3

Cable Management Bracket for - MB600

- Surface Mount
- Operation: For use with LK171-2
- Nail-In anchors not included



LK172-11

Rainshield for F12

- Surface Mount
- Operation : For use with LK1 87-9 & LK1 87-10
- Nail-In anchors not included
- Dimensions: 141 mmx92mmx82mm



LK172-12

Cable Management Bracket for -F12

- Surface Mount
- Operation: For use with LK1 87-9
- Nail-In anchors not included
- Dimensions: 141 mm x 92mm x 82mm



LK172-13

Cable Management Bracket for -F22

- Surface Mount
- Operation : For use with LK1 71 & LK1 71-1
- Nail-In anchors not included
- Dimensions: 21 mm x 130mm x 59mm



LK172-7

Rainshield for F16 and F17

- Surface Mount
- Operation : For use with LK1 72-1 & LK1 72-2
- Nail-In anchors not included
- Dimensions: 200mm x 83mm x 85mm



LK172-8

Cable Management Bracket for -F16-F17

- Surface Mount
- Operation : For use with LK1 72-3
- Nail-In anchors not included
- Dimensions: 198mm x 77mm x 22mm



LK172-14

Rainshield for ProCaptureWP

- Surface Mount
- Operation : For use with LK1 72-4
- Nail-In anchors not included
- Dimensions: 219mm x 110mm x 102mm



LK172-15

Rainshield for FR1500-WP

- Surface Mount
- Operation : For use with LK1 87-8
- Nail-In anchors not included
- Dimensions: 93mm x 162mm x 110mm

Accessories

Whether it be rain, dust or to shield the sensor from the rays of the sun. All brackets are made from metal making them strong and durable.

**LK172-17**

Cable Management Bracket for -FR1500-WP

- Surface Mount
- Operation : For use with LK1 87-8
- Nail-In anchors not included
- Dimensions: 128mm x 80mm x 35mm

**LK179-5**

Cable Management Bracket for -MA300BT

- Surface Mount
- Operation : For use with LK1 79
- Nail-In anchors not included

**LK179-6**

Enclosure for MA300BT

- Surface Mount
- Operation : For use with LK179
- Nail-In anchors not included
- Dimensions : 173mm x 100mm x 68mm

**LK172-16**

Cable Management Bracket for -SF100

- Surface Mount
- Operation : For use with LK1 69-3
- Nail-In anchors not included
- Dimensions: 89mm x 89mm x 33mm

**LK188-11**

Cable Management Bracket for SpeedFaceV5LP

- Surface Mount
- Operation : For use with LK188-8
- Nail-In anchors not included

**LK188-17**

Rainshield for ProfaceXP

- Surface Mount
- Operation : For use with LK188-17
- Nail-In anchors not included

**LK188-37**

Rainshield for SpeedFace M4

- Surface Mount
- Operation : For use with LK188-31
- Nail-In anchors not included
- Dimensions: 219mm x 110mm x 102mm

**LK169-14**

Cable Management Bracket for SF300

- Surface Mount
- Operation : For use with LK169-3
- Nail-In anchors not included
- Dimensions : 112mm x 112mm x 21.2mm

**LK188-28**

Stand for ProFaceXP - Adjustable

- Operation : For use with ProFace-X

**LK188-34-1**

Rainshield for ProMa

- Surface Mount
- Operation : For use with LK1 88-34
- Nail-In anchors not included
- Dimensions: 200mm x 83mm x 85mm

**LK188-34-2**

Cable Management Bracket for ProMa

- Surface Mount
- Operation : For use with LK188-34
- Nail-In anchors not included
- Dimensions: 198mm x 77mm x 22mm

**LK179-9**

SRB Secure Relay Board

- Display: 2 LED indicator
- Built-in Relay: 1
- Input Format: Encrypted Wiegand
- Outputs Contact: Electric lock
- Lock Control Delay: Default 1 s
- Power In: 12V DC, 60mA
- Dimension : 50mm x 40mm x 17 mm

**LK197-9**

Enclosure for IN Bio Controller 12VDC 3Amp PSU -Metal

- Anti-Tamper Housing
- Key Lock
- External LED indicators
- Includes: 12VDC 3Amp ZKTeco Power Supply
- Dimensions: 350mmx300mmx90mm
- Controller not Included

**LK188-25**

TSAGN Universal Turnstile Gooseneck - for SpeedFaceV5ProFaceX

- Operation : For use with ProFace-X

OUTDOORS? RAINING?

We have the **Solution**

Rain Shield and Cable Management



ZKTECO



All-In-One Web Based Security Management Solution



CONTACT US

BRANCHES

Gauteng

Alberton:	087 537 4166
Balfour Park:	011 640 2288
Boksburg:	011 918 8505
Centurion:	012 653 0653
Edenvale:	011 453 0229
Fourways:	011 467 8817
Krugersdorp:	087 092 8100
Linden:	011 888 5666
Longmeadow:	011 454 8009
Lynnwood:	012 460 4550
Midrand:	011 312 7576
Montana:	087 802 3939
Roodepoort:	011 760 1149
Strijdom Park:	011 791 4770
Vanderbijlpark:	016 931 0116
Xavier (JHB South):	011 433 8943
Exports:	087 537 4100

Eastern Cape

East London:	043 735 4537
Gqeberha (PE):	041 364 3885

Free State

Bloemfontein:	051 447 6969
---------------	--------------

KwaZulu Natal

Durban:	031 263 0901
Pietermaritzburg:	087 803 4544
Pinetown:	031 701 3222

Mpumalanga

Emalahleni (Witbank):	013 656 4140
Mbombela (Nelspruit):	013 753 2831

Limpopo

Polokwane:	015 296 0531
------------	--------------

Western Cape

Bellville:	021 949 6330
George:	087 537 4155
Northgate:	021 510 1411
Ottery:	021 745 4989

CUSTOMER SUPPORT

Accounts

email
accounts@regalsecurity.co.za

Sales

email
sales@regalsecurity.co.za

National Support Centre

Tel: 087 802 3920
email
nsc.support@regalsecurity.co.za

Need Technical Support?

Call ANY Regal branch and dial 2

SCAN TO VIEW ALL
REGAL BROCHURES



WhatsApp us on **081 475 5079**

